

Sunset Photo Metallic Paper - 60in x 100ft

Building on our award-winning lineup of inkjet materials, Sunset Photo Metallic Paper represents a breakthrough for inkjet photo papers.



Technical Specifications

Product Type	Inkjet Printable Media
Paper Weight	255 gsm
Thickness	10 mil
Applications - Media	Trade Show Graphics Interior Décor Fine Art Photographs POP/ Indoor Signage
Finish	Metallic Gloss
Ink Type	Aqueous
Media Type	Photo Paper
Core Size	3 in
Width	60 in
Length	100 ft
Units	1 Roll
Edge Loyalty Points Multiplier	1x Edge Points
Double Sided	No
Lifetime Warranty	No
Properties	Description
Material	Resin-coated (RC) photo paper
Gauge	10 mils
Basis Weight	255g
ISO Brightness	78
Opacity	97%
Gloss Level @ 75°	62
Surface Finish	High-gloss, metallic
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Imaging Side	Material is packaged with printable side facing up. Printable surface can be identified by a slight tackiness.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A photo luster, satin or semi-gloss setting is the recommended starting point. However, we recommend a custom ICC profile for optimal results. Please refer to www.lexjet.com for starting-point ICC profiles for some printers.
Finishing/Post Processing	For image stability and permanence it is always recommended that you protect the printed side. This can be done by mounting under glass, clear coating, photographic sleeves or laminating.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Print Environment	72° F (22° C), 50% R.H
Optimal Service Environment	For printing: 60° - 80° F, 50% Relative Humidity.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Service Temp. Range	-40° to 176° F (-40° C to 80° C).
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.